

Signature

BLAM
FRENCH SOUND

Driven by passion.

T20 MG


HIGH RESOLUTION TWEETER

- 20 mm (3/4") pur magnesium dome tweeter
- Super powerful neodymium magnet N48
- High precision Machined Aluminium front plate
- Sound transparent protective grill


TECHNICAL SPECIFICATIONS

Component	Tweeter	
Max power	100 W	
Nominal power	15 W	
Impedance	4 Ω	
Freq. Response	1.5 KHz - 45 KHz	
Sensitivity (2.83 V/1m)	88 dB	
Magnet	Neodymium	
Magnet size \varnothing x h	19.5 x 3 mm	0.748" x 0.118"
Total driver displacement	-	
Weight of one component	0.044 kg	0,097 lb
Voice coil \varnothing	20 mm	0.787"
Voice coil height	4.2 mm	1.157"
Dome	Soft	

FREQUENCY RESPONSE / IMPEDANCE



Unit : mm



THIELE-SMALL PARAMETERS

Effective \varnothing (d)	24 mm
Sd	4.52 cm ²
Xmax	-
Re	3.98 Ω
Fs	2 kHz
Le	-
L2	-
Vas	-
Mms	-
Cms	-
BL	-
Qts	-
Qes	-
Qms	-
Sensitivity (dB/W/m)	84.8 dB

contact@blam-audio.fr
www.facebook.com/blamaudio

blam-audio.com